



SAFETY DATA SHEET

Effective Date: 04/18/2019

Replaces: 11/01/2016

Ready-Mix Concrete

1. Identification	
Product name: Ready Mix Concrete	
Other means of identification/Synonyms/Common Names: Freshly Mixed Unhardened Concrete	
Recommended use: Ready Mix Concrete is used as a construction material.	
Recommended restrictions: None Known	
Manufacturer/Contact info: Pine Bluff Sand and Gravel Company 200 North Kansas St. Pine Bluff, AR 71601	General Phone Number: 1-870-534-7121 Emergency Phone Number (24 hours/day, 7 days/week): US & Canada: 1-800-451-8346 / Contract #16839 Outside US & Canada: +1-760-602-8703 Website: www.pbsgc.com

2. Hazard(s) Identification		
Physical hazards: Not Classified	Health hazards: Skin corrosion/irritation-Category 1B Serious eye damage/eye irritation-Category 1 Carcinogenicity-Category 1A Specific target organ toxicity, single exposure- Category 3 Specific target organ toxicity, repeated exposure- Category 2	
Signal word: Danger		
Hazard Statement: Causes severe skin burns and eye damage Causes serious eye damage May cause cancer (Inhalation) May cause respiratory irritation May cause damage to organs (lung/respiratory system) through prolonged or repeated exposure (inhalation)		
Precautionary statement: Prevention • Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.		

- Do not breathe dust, fume, or vapors. Use only outdoors or in a well-ventilated area.
- Wash hands thoroughly after handling
- Use personal protective equipment as required. Wear protective gloves, protective clothing, eye protection, and face protection.

Response

- If exposed or concerned: Immediately call a Poison Center or doctor/physician. Get medical advice/attention
- Specific treatment (see the following information on this label)
- IF SWALLOWED: Rinse mouth Do NOT induce vomiting.
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse cautiously with water for several minutes. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention.
- IF INHALED: Remove victim to fresh air and keep at rest position comfortable for breathing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- Wash contaminated clothing before reuse.

Disposal

- Dispose of contents/container in accordance with all local, regional, national, and international regulations.

Hazards Not Otherwise Classified:

None Known

Supplemental information:

Ready mix concrete contains a naturally occurring mineral complex with varying quantities of quartz (crystalline silica). Respirable Crystalline Silica (RCS) may cause cancer. Hardened ready mix concrete may be subjected to various natural or mechanical forces that produce small particles (dust), which may contain respirable crystalline silica (particles less than 10 micrometers in aerodynamic diameter). Repeated inhalation of respirable crystalline silica (quartz) may cause lung cancer according to IARC, NTP; ACGIH states that it is a suspected cause of cancer.

3. Composition/information on ingredients

Chemical name	CAS number	%
Aggregate (crushed stone, sand, gravel, expanded shale)	Mixture	60-95
Quartz (crystalline silica)	14808-60-7	>1
Hydraulic Cement(s)	Mixture	3-20
Portland and/or Slag Cement	65997-15-1	
Pozzolan	Mixture	0-11
Artificial Fly Ash	38131-74-8	
Natural Metakaolin and/or	1332-58-7	
Silica Fume	69012-64-2	
Water	7732-18-5	6-13

4. First-aid measures

Inhalation:

Remove person to fresh air. Dust in throat and nasal passages should clear spontaneously. Contact a physician if irritation persists. Dusts from hardened product may irritate the mouth, nose, throat and lungs.

Eyes:

Immediately flush eye(s) with plenty of clean water for at least 30 minutes, while holding the eyelid(s) open. Occasionally lift the eyelid(s) to ensure thorough rinsing. Beyond flushing, do not attempt to remove material from eye(s). Get medical attention.

Skin:

Immediately flush skin with plenty of clean water, for at least 15 minutes, after removing contaminated clothing and shoes. Contact a physician if irritation persists.

Ingestion:

If person is conscious do not induce vomiting. Give large quantity of water and get immediate medical attention. Never attempt to make an unconscious person drink.

Most important symptoms/effects, acute and delayed:

Contact with wet product may result in chemical (caustic) burns and eye injury, which may be progressive and could cause blindness. Wet product may result in chemical burns to the skin. Breathing dust may be severely irritating. Symptoms may include coughing, labored breathing, sneezing and burning sensation, depending on the concentration and duration of exposure. Swallowing this material may cause painful and burning of the mouth and throat, and

damage to the gastrointestinal tract.

Dust from hardened product may irritate the eyes, skin, and respiratory tract. Breathing respirable crystalline silica-containing dust for prolonged periods in the workplace can cause lung damage and a lung disease called silicosis. Symptoms of silicosis may include (but are not limited to) shortness of breath, difficulty breathing with or without exertion; coughing; diminished work capacity; diminished chest expansion; reduction of lung volume; right heart enlargement and/or failure.

Indication of immediate medical attention and special treatment needed:

Not all individuals with silicosis will exhibit symptoms of the disease. However, silicosis can be progressive and symptoms can appear even years after exposures have ceased. Persons with silicosis have an increased risk of pulmonary tuberculosis infection.

For emergencies contact (24 hours/day, 7 days/week):

US & Canada: 1-800-451-8346 / Contract #16839

Outside US & Canada: +1-760-602-8703

5. Fire-fighting measures

Suitable extinguishing media:

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media:

None known

Specific hazards arising from the chemical:

Contact with powerful oxidizing agents may cause fire and/or explosions (see section 10 of SDS).

Special protective equipment and precautions for firefighters:

Use protective equipment appropriate for surrounding materials.

Fire-fighting equipment/instructions:

No unusual fire or explosion hazards noted. Not a combustible dust.

Specific methods:

The presence of this material in a fire does not hinder the use of any standard extinguishing medium. Use extinguishing medium for surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Persons involved in cleanup processes should first observe precautions (as appropriate) identified in Section 8 of this SDS.

For emergencies contact (24 hours/day, 7 days/week):

US & Canada: 1-800-451-8346 / Contract #16839

Outside US & Canada: +1-760-602-8703

Environmental precautions:

Prevent from entering into sewers or drainage systems where it can harden and clog flow.

Methods and materials for containment and cleaning up:

Wet product should be removed from roads or other surfaces where it may interfere with traffic. If hardened material is spilled and dust is generated, cleanup personnel may be exposed to respirable crystalline silica. Do not dry sweep or use compressed air for clean-up. Wetting of spilled material and/or use of respiratory protective equipment may be necessary.

7. Handling and storage

Precautions for safe handling:

Respirable crystalline silica-containing dust may be generated during processing, handling, and storage. Use personal protection and controls identified in Section 8 of this MSDS as appropriate.

Conditions for safe storage, including any incompatibilities:

Do not store near food, beverages, or smoking materials.

8. Exposure controls/personal protection

Legend:

NE = Not Established; PEL = Permissible Exposure Limit; TLV = Threshold Limit Value; REL = Recommended Exposure Limit; STEL= Short Term Exposure Limit; OSHA = Occupational Safety and Health Administration; MSHA = Mine Safety and Health Administration; NIOSH = National Institute for Occupational Safety and Health; ACGIH = American Conference of Governmental Industrial Hygienists; AL=Action Level.

Component	OSHA/MSHA PEL	ACGIH TLV	NIOSH REL
Portland Cement	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)	10 mg/m ³ (inhalable fraction) 3 mg/m ³ (respirable fraction)	NE
Respirable dust containing silica	OSHA: Use Respirable Crystalline Silica PEL MSHA: 10 mg/m ³ ÷ (% silica + 2)	Use Respirable Silica TLV	Use Respirable Silica REL
Total dust containing silica	OSHA: NE MSHA: 30 mg/m ³ ÷ (% silica + 3)	NE	NE
Respirable Crystalline Silica (quartz)	OSHA: 0.05 mg/m ³ (0.025mg/m ³ AL) MSHA 10 mg/m ³ ÷ (% silica + 2)	0.025 mg/m ³	0.05 mg/m ³
Respirable Tridymite and Cristobalite (other forms of crystalline silica)	OSHA: Use PEL for Respirable Crystalline Silica MSHA: Use ½ of respirable dust containing silica PEL	0.025 mg/m ³	0.05 mg/m ³
Amorphous Silica	80 mg/m ³ ÷ % silica	NE	6 mg/m ³
Iron Oxide	10 mg/m ³	5 mg/m ³ (respirable fraction)	5 mg/m ³ (respirable fraction)
Magnesium Oxide	15 mg/m ³ (total dust)	10 mg/m ³ (inhalable fraction)	NE
Aluminum Oxide	15 mg/m ³ (total dust) 5 mg/m ³ (Respirable)	10 mg/m ³ (total dust)	15 mg/m ³ (total dust) 5 mg/m ³ (Respirable)
Manganese Oxide	5 mg/m ³ (as Mn)	0.2 mg/m ³ (as Mn)	1 mg/m ³
Particulates Not Otherwise Classified	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)	10 mg/m ³ (inhalable fraction) 3 mg/m ³ (respirable fraction)	NE

Exposure Guidelines:

Total dust containing silica, respirable silica-containing dust and respirable crystalline silica (quartz) levels should be monitored regularly to determine worker exposure levels. Exposure levels in excess of allowable exposure limits should be reduced by all feasible engineering controls, including (but not limited to) wet suppression, ventilation, process enclosure, and enclosed employee workstations.

Engineering Controls:

Ordinarily not required when working with wet product. Activities that generate dust from hardened product require the use of general ventilation, local exhaust, and/or wet suppression methods adequate to maintain exposures below appropriate exposure limits.

Eye Protection:

Safety glasses with side shields should be worn as minimum protection. Goggles or face shield should be worn where splashing is possible. Dust goggles should be worn when excessively (visible) dusty conditions are present or are anticipated due to working with hardened product

Skin Protection (Protective Gloves/Clothing):

Waterproof gloves, rubber boots, and clothing sufficient to protect skin from contact with wet product should be worn. Clothing saturated from contact with wet product should be removed promptly to prevent continued contact with skin. As a precaution, wash hands thoroughly before eating, smoking, and using toilet facilities. After working with product, workers should clean their skin with soap and water. Clean clothing should be worn after showering.

Respiratory Protection:

Ordinarily not required when working with wet product. Activities that generate dust from hardened dry product require the use of a NIOSH approved respirator for the exposure circumstances involved (See NIOSH Respirator Selection Guide). The need for respiratory protection should be evaluated by a qualified safety and health professional. Activities that generate dust require the use of an appropriate dust respirator where dust levels exceed or are likely to exceed allowable exposure limits. For respirable silica-containing dust levels that exceed or are likely to exceed an 8 hr Time Weighted Average (TWA) of 0.25 mg/m³, a high efficiency particulate filter respirator must be worn at a minimum; however, if respirable silica-containing dust levels exceed or are likely to exceed an 8 hr TWA of 1.25 mg/m³, a positive pressure respirator, full face respirator or equivalent is required. Respirator use must comply with applicable MSHA (42 CFR 84) or OSHA (29 CFR 1910.134) standards, which include provisions for a user training program, respirator inspection, repair and cleaning, respirator fit testing, medical surveillance and other requirements.

9. Physical and chemical properties**Appearance:**

Gray, plastic, flowable, granular mixture.

Odor: Faint, characteristic cement odor.	PH: Approximately 12	Decomposition temperature: Not applicable
Melting point/freezing point: Not applicable	Initial boiling point and boiling range: Not applicable	Flash point: Non-combustible
Evaporation rate: Not applicable	Flammability: Not applicable	Upper/lower flammability or explosive limits: Not applicable
Vapor pressure: Not applicable	Relative density: Not applicable	Solubility: 0.1 - 1%
Partition coefficient: n-octanol/water. Not applicable	Autoignition temperature: Not applicable	Specific Gravity (H₂O = 1): 1.7 - 3.0

10. Stability and reactivity**Reactivity:**

Not reactive under normal use.

Chemical stability:

Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

None under normal use.

Conditions to avoid (e.g., static discharge, shock or vibration):

Contact with incompatible materials should be avoided (see below). See Sections 5 and 7 for additional information.

Incompatible materials:

Fresh concrete is caustic (pH approximately 12) and could react with strong acids. Silica reacts violently with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride yielding possible fire and/or explosions. Silica dissolves readily in hydrofluoric acid producing a corrosive gas - silicon tetrafluoride.

Hazardous decomposition products:

Respirable crystalline silica-containing dust may be generated. When heated, quartz is slowly transformed into tridymite (above 860°C/1580°F) and cristobalite (above 1470°C/2678°F). Both tridymite and cristobalite are other forms of crystalline silica.

11. Toxicological information**Primary Routes of Exposure:**

Inhalation and contact with the eyes and skin.

Symptoms related to the physical, chemical, toxicological characteristics:**Inhalation:**

Not expected to be a significant exposure route. Dusts from hardened product may irritate the mouth, nose, throat and lungs. Coughing, sneezing and shortness of breath may occur.

Symptoms of silicosis may include (but are not limited to) shortness of breath, difficulty breathing with or without

exertion; coughing; diminished work capacity; diminished chest expansion; reduction of lung volume; right heart enlargement and/or failure. Persons with silicosis have an increased risk of pulmonary tuberculosis infection.

Eye Contact:

Contact may result in chemical (caustic) burns and eye injury which may be progressive and could cause blindness. Symptoms may include tearing, redness, pain, swelling with blurred vision. Dusts from hardened product may be irritating.

Skin Contact:

May cause severe skin irritation with redness, pain, an itching or burning feeling, and swelling of the skin. More severe effects, including chemical (alkali) burns and skin ulcers may occur. Dusts from hardened product may be irritating and cause dermatitis after prolonged or repeated exposure.

Ingestion:

Direct contact with exposed tissues may result in severe irritation with pain, nausea, vomiting, and/or diarrhea and possibly chemical (alkali) burns.

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Hydraulic (Portland) cement may contain trace amounts of hexavalent chromium. Hexavalent chromium has been associated in some individuals with causing allergic reactions which may be manifested as contact dermatitis and skin ulcerations. Individuals who develop allergies to skin sensitizers such as hexavalent chromium, may experience a reaction upon repeated contact with those compounds. Irritated or broken skin is more likely to develop further complications such as ulcers and infection. Dermatitis and allergic reactions have been observed in workers with chronic exposure to fly ash. This was attributed to trace amounts of chromium, cobalt, nickel and other metals in the fly ash.

The following information pertains to creating dust from hardened dry material:

Prolonged overexposure to respirable dusts in excess of allowable exposure limits can cause inflammation of the lungs leading to possible fibrotic changes, a medical condition known as pneumoconiosis.

Prolonged and repeated overexposure to high levels of respirable crystalline silica-containing dust may cause a chronic form of silicosis, an incurable lung disease that may result in permanent lung damage or death. Chronic silicosis generally occurs after 10 years or more of overexposure; a more accelerated type of silicosis may occur between 5 and 10 years of higher levels of prolonged and repeated overexposure. In early stages of silicosis, not all individuals will exhibit symptoms (signs) of the disease. However, silicosis can be progressive, and symptoms can appear at any time, even years after exposure has ceased.

Repeated overexposures to very high levels of respirable crystalline silica for periods as short as six months may cause acute silicosis. Acute silicosis is a rapidly progressive, incurable lung disease that is typically fatal. Symptoms include (but are not limited to): shortness of breath, cough, fever, weight loss, and chest pain.

Respirable dust containing newly broken crystalline silica particles has been shown to be more hazardous to animals in laboratory tests than respirable dust containing older crystalline silica particles of similar size. Respirable crystalline silica particles which had aged for sixty days or more showed less lung injury in animals than equal exposures to respirable dust containing newly broken particles of respirable crystalline silica.

There are reports in the literature suggesting that excessive respirable crystalline silica exposure may be associated with autoimmune disorders and other adverse health effects involving the kidney. In particular, the incidence of scleroderma (thickening of the skin caused by swelling and thickening of fibrous tissue) appears to be higher in silicotic individuals. To date, the evidence does not conclusively determine a causal relationship between silica exposure and these adverse health effects.

Carcinogenicity:

Epidemiology studies on the association between respirable crystalline silica exposure and lung cancer have had both positive and negative results. There is some speculation that the source, type, and level of exposure of respirable crystalline silica may play a role. Studies of persons with silicosis indicate an increased risk of developing lung cancer, a risk that increases with the level and duration of exposure. It is not clear whether lung cancer develops in non-silicotic patients. Several studies of silicotics do not account for lung cancer confounders, especially smoking, which have been shown to increase the risk of developing lung disorders, including emphysema and lung cancer.

In October 1996, an IARC Working Group designated respirable crystalline silica as carcinogenic (Group 1). In 2012, an IARC Working Group re-affirmed that inhalation of crystalline silica was a known human carcinogen. The NTP's Report

on Carcinogens, 9th edition, lists respirable crystalline silica as a "known human carcinogen." In the year 2000, the American Conference of Governmental Industrial Hygienists (ACGIH) listed respirable crystalline silica (quartz) as a suspected human carcinogen (A-2). These classifications are based on sufficient evidence of carcinogenicity in certain experimental animals and on selected epidemiological studies of workers exposed to respirable crystalline silica.

Additional information on toxicological-effects:

Acute toxicity: Not classified

Skin corrosion/irritation: Causes severe skin burns and eye damage

Serious eye damage/eye irritation: Causes serious eye damage.

Respiratory sensitization: Not classified.

Skin sensitization: Not classified.

Germ cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Reproductive toxicity: Not classified

Specific target organ toxicity - single exposure: May cause respiratory irritation

Specific target organ- toxicity – repeated exposure: May causes damage to organs (lungs, respiratory system) through prolonged or repeated exposure (inhalation)

Aspiration toxicity: Not classified (not applicable- solid material)

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Not applicable

Persistence and degradability:

Not applicable

Bioaccumulative potential.

Not applicable

Mobility in soil.

Not applicable

Other adverse effects.

Not applicable

13. Disposal considerations

Safe handling and disposal of waste:

Material can be retained until it hardens, and then disposed of as solid waste. Place contaminated materials in appropriate containers and dispose of in a manner consistent with applicable federal, state, and local regulations. Prevent from entering drainage, sewer systems, and unintended bodies of water. It is the responsibility of the user to determine, at the time of disposal, whether product meets criteria for hazardous waste. Product uses, transformations, mixture and processes, may render the resulting material hazardous.

14. Transport information

UN Number:

Not regulated

UN Proper shipping name:

Not regulated

Transport Hazard class:

Not applicable

Packing group, if applicable:

Not applicable

Marine pollutant (Yes/No):

Not applicable

15. Regulatory information
Toxic Substances Control Act (TSCA): The components in this product are listed on the TSCA Inventory or are exempt.
Comprehensive Environmental Response, Compensation and Liability Act (CERCLA): Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act.
Superfund Amendments and Reauthorization Act of 1986 (SARA), Title III: Section 302 extremely hazardous substances: None Section 311/312 hazard categories: Delayed Health Section 313 reportable ingredients at or above de minimis concentrations: None
California Proposition 65: This product contains a chemical (crystalline silica, chromium, cobalt, nickel) known to the State of California to cause cancer.
State Regulatory Lists: Each state may promulgate standards more stringent than the federal government. This section cannot encompass an inclusive list or all state regulations. Therefore, the user should review the components listed in Section 2 and consult state or local authorities for specific regulations that apply.

16. Other information
Disclaimer
NO WARRANTY IS MADE, EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. Pine Bluff Sand and Gravel Company and its subsidiaries and affiliates (“PBSGC”) believe the information contained herein is accurate; however, PBSGC makes no guarantees with respect to such accuracy and assumes no liability whatsoever in connection with the use of any information contained herein by any party. The provision of the information contained herein is not intended to be, and should not be construed as, legal advice or as ensuring compliance with any federal, state, or local laws, rules or regulations. Any party using any information contained herein should review all applicable laws, rules and regulations prior to use.
Issue date: 01-November-2016
Revision date: 18-April-2019

Pine Bluff Sand and Gravel Company
200 North Kansas St.
Pine Bluff, AR 71601